

- Temperature can easily be set, stepped, and slewed
- Multiple user-defined temperature tables can be stored in memory
- Full 20-character by 4-line alpha/numeric display and keypad
- Actual measured temperature displayed
- Failsafe sensor with easily set limits
- Over-temperature sensor protects against thermal run-away
- Remote operation via IEEE-488 bus or RS-232C communication link
- TTL I/O lines for remote device control



SPECIFICATIONS

Temperature Range:

-55° to +200° C / LCO₂

-65° to +200° C / LN₂

Rate of Temperature Change (Unloaded):

15° C / min. (Standard Option), 30° C / min. (Fast Option)

Stability:

± 0.2° C

(including effects of line voltage, ambient temperature between 15° and 45° C, and aging)

Uniformity:

± 0.5° C from -55° to +125° C

± 1° C to extremes

(Measurements taken from within 1" [2.54 cm] of chamber walls)

The Roditi International Corporation Ltd

Machiavelli House, 102 Stewarts Road, London SW8 4UG. Tel: +44 (0) 20 7819 8080

Fax: +44 (0) 20 7720 5261. e-mail: saunders@roditi.com www.roditi.com

TEMPERATURE CONTROL

- Resistance of platinum resistance sensor converted to digital values
- Internally stored mathematical polynomials convert digital values to temperature
- Calibrated digitized temperature compared to user-set temperature
- Four-point calibration provides greater accuracy

FIXTURE OPTIONS

- Cable ports customized to user specifications

CHARACTERISTICS

Voltage:

190-250 VAC, 50-60 Hz, 4.6 KVA maximum (Standard Heat), 9.5 KVA maximum (Fast Heat)

Dimensions:

Internal:	External: (excluding latches and hinges)
24.00 inches wide (61.0 cm)	37.3 inches wide (94.7 cm)
18.00 inches deep (45.7 cm)	32.3 inches deep (82.0 cm)
18.00 inches high (45.7 cm)	24 inches high (61.0 cm)

Weight:

134 lbs. (60.8 kg.)

Coolant Options:

LCO₂ or LN₂

LCO₂ Usage:

10 lbs/hr at -55° C, typical

The Roditi International Corporation Ltd is the exclusive European representative of Saunders & Associates, LLC