


- Quartz Crystal SMD devices are adjusted to target frequency by Ion Beam Etching of the electrode material
- The motional parameters of the crystal remain virtually unchanged
- Sixty four (64) parts are processed simultaneously for high system throughput
- Small crystal electrodes are as easy to precisely adjust as large electrodes
- Super High Drive capability
- Measured parameters are checked against easy to define Q.C. limits



Transport Boat

- Supports small SMD sizes including 3.2x5.0, 3.2x2.5, 2.5x2.0, 2.0x1.6, 1.6x1.25
- Transport boats carry SMD devices in 16x20 S&A flip pallets
- Dual boat configuration holds four pallets per run with a total of 1280 parts

## SPECIFICATIONS

**250B-1 Frequency Range:**

15 KHz to 220 MHz

**250C Frequency Range:**

15 KHz to 500 MHz

**Etching Performance:**

± 1 ppm typical final frequency

## The Roditi International Corporation Ltd


Machiavelli House, 102 Stewarts Road, London SW8 4UG. Tel: +44 (0) 20 7819 8080

Fax: +44 (0) 20 7720 5261. e-mail: [saunders@roditi.com](mailto:saunders@roditi.com) [www.roditi.com](http://www.roditi.com)

## SYSTEM CONFIGURATION

- Four S&A 250B-1 or 250C Network Analyzers
- Direct Drive Roughing Pump
- Cryo Pump
- Two S&A Dual Channel High Drive Units
- Two S&A Ion Guns
- Two Loading Platforms
- Computer
- *Windows*® based System Software
- Light Pole

## SCREEN FORMAT



## FACILITY REQUIREMENTS

- **Power:** 380VAC/208VAC  
3-Phase, 7KVA, 50/60 Hz
- **Inlet Pressure:** 90 - 100 PSIG  
**Air:** 90 - 100 PSIG  
**Nitrogen:** 70 - 100 PSIG  
**Process Gas:** 20 PSIG
- **Dimensions:** Standard: W 65" x D 37" x H 106"  
With Platform: W 65" x D 52" x H 106"

The Roditi International Corporation Ltd is the exclusive European representative of Saunders & Associates, LLC