


- Quartz Crystal SMD devices are adjusted to target frequency by Ion Beam Etching of the electrode material
- The motional parameters of the crystal remain virtually unchanged
- Sixty four (64) parts are processed simultaneously for high system throughput
- Small crystal electrodes are as easy to precisely adjust as large electrodes
- Super High Drive capability
- Measured parameters are checked against easy to define Q.C. limits



Transport Boat

- Supports small SMD sizes including 3.2x5.0, 3.2x2.5, 2.5x2.0, 2.0x1.6, 1.6x1.25
- Transport boats carry SMD devices in 16x20 S&A flip pallets
- Dual boat configuration holds four pallets per run with a total of 1280 parts

SPECIFICATIONS

250B-1 Frequency Range:

15 KHz to 220 MHz

250C Frequency Range:

15 KHz to 500 MHz

Etching Performance:

± 1 ppm typical final frequency

The Roditi International Corporation Ltd


Machiavelli House, 102 Stewarts Road, London SW8 4UG. Tel: +44 (0) 20 7819 8080

Fax: +44 (0) 20 7720 5261. e-mail: saunders@roditi.com www.roditi.com

SYSTEM CONFIGURATION

- Four S&A 250B-1 or 250C Network Analyzers
- Direct Drive Roughing Pump
- Cryo Pump
- Two S&A Dual Channel High Drive Units
- Two S&A Ion Guns
- S&A 690B-X2 Elevator
- Computer
- *Windows*® based System Software
- Light Pole

SCREEN FORMAT



FACILITY REQUIREMENTS

- **Power:** 380VAC/208VAC
3-Phase, 7KVA, 50/60 Hz
- **Inlet Pressure:** 90 - 100 PSIG
Air: 90 - 100 PSIG
Nitrogen: 70 - 100 PSIG
Process Gas: 20 PSIG
- **Dimensions:** Standard: W 65" x D 37" x H 106"
With Elevator: W 65" x D 59" x H 106"

The Roditi International Corporation Ltd is the exclusive European representative of Saunders & Associates, LLC